



SIZE	L ₁	L	P	D	H	W	A	Q.TY
13Su	68	60	15	31	112	60	41.5	
20Su	76	66	20	36	115	60	45.5	
25Su	82	70	25	46	122	60	50	

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 3.5 MPa (35.7 kgf/cm ²)
△ PRESS.	MAX 2.0 MPa (20.4 kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
△ TEMP.	MAX 100℃	AIR	(kgf/cm ²)

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
△ 19	PLAIN WASHER	1	SUS 304	
△ 18	O RING	1	FKM	
△ 17	WARNING LABEL	1	PAPER	
△ 16	CONICAL WASHER	2	JFE443CT	
△ 15	RUBER PACKING	2	SYNTHETIC RUBBER (HNBR)	
△ 14	NUT	2	SCS 13	
△ 13	HEXAGON NUT	1	SUS 304	
△ 12	NAME PLATE	1	A1050P	
△ 11	HAND WHEEL	1	FC 200	
△ 10	GLAND PACKING	1	ALAMIDE FIBER (V#B133)	
△ 9	STOP RING	1	SUS 304	
△ 8	GASKET	1	P.T.F.E.	
△ 7	GLAND NUT	1	SUS 304	
△ 6	GLAND	1	SUS 304	
△ 5	STEM HOLDER	1	SUS 304	
△ 4	STEM	1	SUS 304	
△ 3	DISC	1	SCS 13	
△ 2	BONNET	1	SCS 13	
△ 1	BODY	1	SCS 13	

NAME NICE JOINT ENDS GATE VALVES			
TYPE	NJ-670	SIZE	13~25Su
DWG.No.	GASS-0055	APPROVED BY	<i>R. Yuzuki</i>
DATE	OCT. 18. 2001	CHECKED BY	<i>H. Arakawa</i>
SCALE	:	DESIGNED BY	
THIRD ANGLE PROJECTION METHOD		DRAWN BY <i>M. Ishai</i>	

△ 使用圧力、使用温度追加	H24. 1. 13.
△ 検査圧力の変更	H23. 2. 9.
△ 皿ワッシャ材質変更	H22. 2. 10.
△ 平ワッシャ追加	H21. 12. 1.
△ ナットをロスト製に変更	H19. 12. 26.

O. N. INDUSTRIES LTD.