



SIZE	d	L	D	T	BOLT HOLE			H	W	A	E	B	D ₁	C ₁	n ₁	h ₁	F	Q, TY
					C	n	h											
50	50	134	155	16	120	4	19	155	320	33	31	175	90	140	6	M12	5.1	
65	65	143	175	18	140	4	19	162	320	38	37	195	102	160	6	M16	5.1	

SPEC.		TEST PRESS.	
FLUID		SHELL	H ₂ O 2.1 MPa (21.4 kgf/cm ²)
PRESS.	(MPa / kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
TEMP.	°C	AIR	MPa (kgf/cm ²)

END FLANGED: JIS B 2220

19	GLAND SLEEVE	1	SUS 316	
18	STUD BOLT, NUT	6	SUS 304	
17	GLAND BOLT	2	SUS 304	
16	BODY CAP BOLT	*4	SUS 304	*65A:6
15	HANDLE	1	FCD 450	
14	STOP RING	1	SUS 304	
13	STOPPER	1	SUS 304	
12	STEM BEARING	1	P.T.F.E.	GLASS FILLED
11	GLAND PACKING	1 _{SET}	P.T.F.E.	
10	THRUST BEARING	1	P.T.F.E.	GLASS FILLED
9	GASKET PACKING	1	P.T.F.E.	
8	BALL SEAT	2	P.T.F.E.	GLASS FILLED
7	PAD PACKING	1	P.T.F.E.	GLASS FILLED
6	GLAND	1	SCS 13	
5	STEM	1	SUS 316	
4	BALL DISC	1	SCS 14A	
3	TANK PAD	1	SCS 14A	
2	BODY CAP	1	SCS 14A	
1	BODY	1	SCS 14A	

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
NAME JIS 10 K F.F. FLANGED END STRAIGHT WAY TANK BALL VALVES				
TYPE	N-765	SIZE	50, 65 A	
DWG.No.	BABS-0278	APPROVED BY	R. Yumoto	
DATE	APR.02.2007.	CHECKED BY	H. Kido	
SCALE	:	DESIGNED BY	K. Takahara	
THIRD ANGLE PROJECTION METHOD DRAWN BY K. Takahara				

O. N. INDUSTRIES LTD.