



SIZE	d	D	T	BOLT HOLE			H	L	Q.TY
				C	n	h			
65A	65	175	18	140	4	19	176	180	
80A	80	185	18	150	8	19	198	217	
100A	100	210	18	175	8	19	240	244	
125A	125	250	20	210	8	23	275	291	
150A	150	280	22	240	8	23	334	340	
200A	200	330	22	290	12	23	445	415	
250A	250	400	24	355	12	25	520	470	
300A	300	445	24	400	16	25	611	556	

SPEC.		TEST PRESS.	
FLUID		SHELL 65~150A	HYORO 2.1 MPa (21.4kgf/cm <sup>2</sup> )
PRESS.	MPa ( kgf/cm <sup>2</sup> )	SHELL 200~300A	HYORO 1.5 MPa (15.3kgf/cm <sup>2</sup> )
TEMP.	°C	SEAT AIR	0.6 MPa (6.1 kgf/cm <sup>2</sup> )

END FLANGE : JIS B 2220

No.6 300A Q.TY: 14

No.6 200A, 250A Q.TY: 12

No.6 65A Q.TY: 6

9	BEARING	2	P.T.F.E	+SUS316
8	GASKET PACKING	1	P.T.F.E	
7	O RING	1	NBR	
6	HEXAGON BOLT	8	SUS 316	
5	PIN	1	SUS 316	
4	DISC	1	SCS 14A	
3	SEAT	1	SCS 14A	
2	STRAINER	1	SCS 14A	
1	BODY	1	SCS 14A	
No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS

NAME	JIS 10K FLANGED END FOOT VALVES		
TYPE	N-215	SIZE	65A~300A
DWG.No.	FAFS-0160	APPROVED BY	<i>H. Tamoto</i>
DATE	APR. 12. 2007.	CHECKED BY	<i>M. Kono</i>
SCALE	:	DESIGNED BY	
THIRD ANGLE PROJECTION METHOD	DRAWN BY	<i>H. Takahashi</i>	

**O. N. INDUSTRIES LTD.**