


SIZE	d	P	L	L ₁	L ₂	H ₁	H ₂	W	D	Q, TY
20Sux3/4	Rc 3/4	20	88.5	47.5	41	101	46	130	47	
25Sux1	Rc 1	25	95.5	49.5	46	104	46	130	54	

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 3.5 MPa
PRESS.	MAX 2.0 MPa	SEAT	AIR 0.6 MPa
TEMP.	MAX 100 °C	AIR	MPa



PIPE THREADS CONFORM WITH "JIS B 0203"
*MODIFIED P.T.F.E.

18	O RING	1	FKM	
17	LOOSE STOPPER	1	SUS 304CSP	
16	RUBBER PACKIG	1	SYNTHETIC RUBBER (NJSR)	
15	RATCHET NUT	1	SCS 13	
14	HEXAGON NUT	1	SUS 304	
13	SPRING WASHER	1	SUS 304	
12	HANDLE	1	SUS 304	
11	GLAND PACKING	1	P.T.F.E.	
10	BEARING	1	P.T.F.E.	CARBON FILLED
9	GASKET PACKING	2	P.T.F.E.	
8	BALL SEAT	2	P.T.F.E.	*
7	WASHER	1	SUS 304CSP	
6	GLAND BUSHING	1	SCS 13	
5	STEM	1	SUS 304	
4	BALL DISC	1	SCS 13A	
3	BODY CAP (B)	1	SCS 13	Rc "d"
2	BODY CAP (A)	1	SCS 13	
1	BODY	1	SCS 13	

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
NAME NICE JOINT AND SCREWED ENDS FULL BORE LONG NECK TYPE MINI BALL VALVES				
TYPE NJX-222NF		SIZE 20, 25Su		
DNG.No. XBAMS-0028◇		DATE NOV. 6, 2023		
APPROVED	DESIGNED	CHECKED	DRAWN	

THIRD ANGLE PROJECTION METHOD SCALE :			
O. N. INDUSTRIES LTD.			