


◇ 1660-0931 BAMS-0931



PVC COATING

SIZE	PIPE THREADS	P	L	H ₁	H ₂	W	D	Q. TY
1/2	Rc 1/2	10	60	86.5	45	100	30.5	
3/4	Rc 3/4	15	70	90	45	100	38	
1	Rc 1	20	80	99.5	45	130	46.5	

SPEC.		TEST PRESS.	
FLUID		SHELL	WATER 8.24 MPa (84 kgf/cm ²)
PRESS.	MPa (kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
TEMP.	℃	AIR	MPa (kgf/cm ²)


PIPE THREADS CONFORM WITH "JIS B 0203"

14	PLAIN WASHER	1	SUS 304	
13	HEXAGON NUT	1	SUS 304	
12	SPRING WASHER	1	SUS 304	
11	HANDLE	1	SUS 304	
10	GLAND PACKING	1	P.T.F.E.	
9	BEARING	1	P.T.F.E.	CARBON FILLED
8	GASKET PACKING	2	P.T.F.E.	
7	BALL SEAT	2	P.T.F.E.	
6	WASHER	1	SUS 316	
5	GLAND BUSHING	1	SCS 13	
4	STEM	1	SUS 304	
3	BALL DISC	1	SCS 13A	1/2: SUS 304
2	BODY CAP	2	SCS 13	
1	BODY	1	SCS 13	

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
NAME	800 W.O.G. SCREWED ENDS REGULAR BORE LONG NECK TYPE BALL VALVES			
TYPE	N-200	SIZE	1/2 ~ 1 B	
DWG. No.	BAMS-0931 ◇	APPROVED BY	H. Ogura	
DATE	AUG. 27. 2007	CHECKED BY	H. Ogura	
SCALE		DESIGNED BY	M. Yamashita	
THIRD ANGLE PROJECTION METHOD		DRAWN BY	T. OKAMOTO	

O. N. INDUSTRIES LTD.




- 13
- 12
- 14
- 11
- 5
- 6
- 10
- 9
- 4
- 3
- 7
- 1
- 8
- 2



△		
△		
△		

DMG No. BAMS-0932

Q. TY: _____



SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 8.24 MPa
PRESS.	MPa	SEAT	AIR 0.6 MPa
TEMP.	℃	AIR	MPa

PIPE THREADS CONFORM WITH 'JIS B 0203'

14	PLAIN WASHER	1	SUS 304	
13	HEXAGON NUT	1	SUS 304	
12	SPRING WASHER	1	SUS 304	
11	HANDLE	1	SUS 304	
10	GLAND PACKING	1	P.T.F.E.	
9	BEARING	1	P.T.F.E.	CARBON FILLED
8	GASKET PACKING	2	P.T.F.E.	
7	BALL SEAT	2	P.T.F.E.	
6	WASHER	1	SUS 316	
5	GLAND BUSHING	1	SCS 13	
4	STEM	1	SUS 304	
3	BALL DISC	1	SCS 13A	
2	BODY CAP	1	SCS 13	
1	BODY	1	SCS 13	

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
NAME	800 W.O.G. SCREWED ENDS REGULAR BORE LONG NECK TYPE BALL VALVE			
TYPE	N-200	SIZE	1 1/4" B	
DMG. No.	BAMS-0932	DATE	AUG. 27. 2007.	
THIRD ANGLE PROJECTION METHOD		SCALE		
APPROVED	CHECKED	DESIGNED	DRAWN	


--	--	--	--

O. N. INDUSTRIES LTD.



	キトップ形状修正	2025. 4. 25.
--	----------	--------------

◇ 3360-SWAB 0000

SIZE	PIPE THREADS	P	L	H ₁	H ₂	W	D	Q. TY
1 1/2	Rc 1 1/2	32	100	119	45	170	67	
2	Rc 2	40	120	125	45	170	80	



SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 8.24 MPa
PRESS.	MPa	SEAT	AIR 0.6 MPa
TEMP.	°C	AIR	MPa



PIPE THREADS CONFORM WITH 'JIS B 0203'

14	PLAIN WASHER	1	SUS 304	
13	HEXAGON NUT	1	SUS 304	
12	SPRING WASHER	1	SUS 304	
11	HANDLE	1	SUS 304	
10	GLAND PACKING	1	P.T.F.E.	
9	BEARING	1	P.T.F.E.	CARBON FILLED
8	GASKET PACKING	2	P.T.F.E.	
7	BALL SEAT	2	P.T.F.E.	
6	WASHER	1	SUS 316	
5	GLAND BUSHING	1	SCS 13	
4	STEM	1	SUS 304	
3	BALL DISC	1	SCS 13A	
2	BODY CAP	1	SCS 13	
1	BODY	1	SCS 13	

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
	800 W.O.G. SCREWED ENDS REGULAR BORE LONG NECK TYPE BALL VALVE			
NAME	N-200	SIZE	1 1/2 B, 2B	
DWG. No.	BAMS-0933 ◇	DATE	AUG. 27. 2007.	
THIRD ANGLE PROJECTION METHOD		SCALE		
APPROVED	CHECKED	DESIGNED	DRAWN	

--	--	--	--

O. N. INDUSTRIES LTD.

△		
△		
△	キャップ形状修正	2025.4.25.