



Q. TY: _____

SPEC .		TEST PRESS.	
FLUID		SHELL	HYDRO 2.1 MPa (21.4kgf/cm ²)
PRESS.	MPa (kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
TEMP.	°C	AIR	MPa (kgf/cm ²)

END FLANGED : JIS B 2220

19	GLAND SLEEVE	1	SUS 316	
18	STUD BOLT, NUT	4	SUS 304	
17	GLAND BOLT	2	SUS 304	
16	BODY CAP BOLT	4	SUS 304	
15	HANDLE	1	SCS 13	
14	STOP RING	1	SUS 304	
13	STOPPER	1	SUS 304	
12	STEM BEARING	1	P.T.F.E.	GLASS FILLED
11	GLAND PACKING	1SET	P.T.F.E.	
10	THRUST BEARING	1	P.T.F.E.	GLASS FILLED
9	GASKET PACKING	1	P.T.F.E.	
8	BALL SEAT	2	P.T.F.E.	GLASS FILLED
7	PAD PACKING	1	P.T.F.E.	GLASS FILLED
6	GLAND	1	SCS 13	
5	STEM	1	SUS 304	
4	BALL DISC	1	SCS 13A	
3	TANK PAD	1	SCS 13A	
2	BODY CAP	1	SCS 13A	
1	BODY	1	SCS 13A	

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
NAME JIS 10 K F.F. FLANGED END STRAIGHT WAY TANK BALL VALVE				
TYPE N-765		SIZE	40 A	
DWG.No.	BABS-0273	APPROVED BY	<i>K. Jemata</i>	
DATE	APR.02.2007	CHECKED BY	<i>A. Adhikari</i>	
SCALE	:	DESIGNED BY	-	
THIRD ANGLE PROJECTION METHOD		DRAWN BY	<i>K. Jemata</i>	

O. N. INDUSTRIES LTD.