



SIZE	FLANGE SIZE	d	P	L	D	T	T ₁	G	BOLT HOLE			H	W	A	B	B ₁	E	F	Q, TY
									C	n	h								
80	100	80	65	200	210	18	30.5	151	175	8	19	169	320	112	65	78	Rp 3/4	5.1	
100	150	100	80	230	280	22	37.5	212	240	8	23	210	400	128	65	81	Rp 3/4	5.1	

SPEC .		TEST PRESSURE	
FLUID		SHELL	HYDRO 2.1 MPa (21.4kgf/cm ²)
PRESS.	MPa (kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
TEMP.	°C	JACKET	AIR 0.6 MPa (6.1 kgf/cm ²)

END FLANGED : JIS B 2220

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
18	SOCKET BOLT	4	SUS 304	
17	DRAIN PLUG	1	SCS 13	R3/4
16	JACKET	1	SCS 13A	
15	GLAND BOLT	2	SUS 304	
14	HANDLE	1	FCD 450	
13	STOP RING	1	SUS 304	
12	STOPPER	1	SUS 304	
11	BEARING	1	P.T.F.E.	+SUS 316
10	GLAND PACKING	1SET	P.T.F.E.	CARBON FILLED
9	GASKET PACKING	1	P.T.F.E.	CARBON FILLED
8	BALL SEAT	2	P.T.F.E.	GLASS FILLED
7	THRUST RING	1	SUS 329J1	
6	GLAND	1	SCS 13	
5	GLAND SLEEVE	1	SUS 316	
4	STEM	1	SUS 304	
3	BALL DISC	1	SCS 13A	
2	SEAT HOLDER	1	SCS 13A	
1	BODY	1	SCS 13A	

NAME	JIS 10 K R.F. FLANGED ENDS JACKET TYPE STRAIGHT WAY BALL VALVES		
TYPE	N-7017	SIZE	80, 100 A
DWG.No.	BAJS-0653	APPROVED BY	<i>K. Yamato</i>
DATE	DEC. 19. 2006.	CHECKED BY	<i>Sh. Akiyoshi</i>
SCALE	:	DESIGNED BY	<i>R. Matsuda</i>
THIRD ANGLE PROJECTION METHOD		DRAWN BY	

△ ボールシート材質・平面図変更 '07.04.04.

O. N. INDUSTRIES LTD.