



SIZE	PIPE THREADS	P	L	H	W	D	Q, TY
	d						
3/8	Rc 3/8	8	55	49	100	27	
1/2	Rc 1/2	10	60	50	100	30	
3/4	Rc 3/4	15	70	54	100	38	
1	Rc 1	20	80	64	130	46.5	
1 1/4	Rc 1 1/4	25	90	68	130	54	

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 8.24 MPa
PRESS.	MPa	SEAT	AIR 0.6 MPa
TEMP.	℃	AIR	MPa

PIPE THREADS CONFORM WITH 'JIS B 0203'
 No.3 3/8, 1/2 B MATERIAL: SUS 304

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
12	HEXAGON NUT	1	SUS 304	
11	SPRING WASHER	1	SUS 304	
10	HANDLE	1	SUS 304	
9	THRUST BEARING	1	P.T.F.E.	CARBON FILLED
8	THRUST PACKING	1	P.T.F.E.	CARBON FILLED
7	GASKET PACKING	1	P.T.F.E.	
6	BALL SEAT	2	P.T.F.E.	
5	GLAND	1	SUS 304	
4	STEM	1	SUS 304	
3	BALL DISC	1	SCS 13A	
2	BODY CAP	1	SCS 13	
1	BODY	1	SCS 13	

NAME	800 W.O.G. SCREWED ENDS MINI BALL VALVES REGULAR BORE		
TYPE	N-610	SIZE	3/8 ~ 1 1/4 B
DMG.No.	BAMS-0926	APPROVED BY	H. Ogawa
DATE	APR. 12. 2007	CHECKED BY	H. Ogawa
SCALE	:	DESIGNED BY	R. Matsumi
THIRD ANGLE PROJECTION METHOD		DRAWN BY	Y. Katayama

O. N. INDUSTRIES LTD.

△		
△		
△	材質変更	2021. 2. 1