


◇ BATS-0921 DWG. No.



SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 2.1 MPa (21.4kgf/cm ²)
PRESS.	MPa (kgf/cm ²)	SEAT	AIR 0.6 MPa (6.1 kgf/cm ²)
TEMP.	°C	AIR	MPa (kgf/cm ²)

END FLANGED : JIS B 2220

19	COVER BOLT	6	SUS 304	
18	HEXAGON NUT	12	SUS 304	
17	STUD BOLT	12	SUS 304	
16	STOP RING	1	SUS 304	
15	HANDLE	1	SCS 13	
14	STOPPER	1	SS 400	
13	DRAIN PLUG	3	SUS 304	
12	O RING	2	VITON	
11	O RING	1	VITON	
10	SEAT PACKING	3	VITON	
9	BEARING	1	P.T.F.E.	GLASS FILLED
8	BEARING	1	P.T.F.E.	GLASS FILLED
7	GASKET PACKING	3	P.T.F.E.	
6	BALL SEAT	3	P.T.F.E.	
5	STOPPER PIN	1	SUS 304	
4	BALL DISC	1	SCS 13A	
3	BODY COVER	1	SCS 13A	
2	BODY CAP	3	SCS 13A	
1	BODY	1	SCS 13A	

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
NAME JIS 10K R.F. FLANGED ENDS				
Y TYPE THREE WAY BALL VALVES				
TYPE	N-736-11	SIZE	40A	
DWG.No.	BATS-0921 ◇	APPROVED BY	<i>K. Sumoto</i>	
DATE	APR. 20. 2007.	CHECKED BY	<i>W. A. K. S. M.</i>	
SCALE	:	DESIGNED BY		
THIRD ANGLE PROJECTION METHOD		DRAWN BY <i>K. Schumaker</i>		

O. N. INDUSTRIES LTD.