



SIZE	d	L	D	Q.TY
350A	270	185	421	
400A	310	191	484	
450A	356	204	539	
500A	387	220	594	

FACE TO FACE: API SPEC 6D
 No.15 350A, 400A : M16, 450A, 500A : M20
 No.17 350 A Q'TY: 12

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
17	HEXAGON BOLT	8	SUS 304	
16	O RING	1	NBR	
15	EYE BOLT	1	S45C	
14	SPRING	2	SUS 316WPA	
13	GASKET PACKING	2	P.T.F.E.	
12	BEARING	2	P.T.F.E.	+SUS 316
11	BEARING	2	P.T.F.E.	+SUS 316
10	HINGE COVER	2	SUS 304	
9	SPACER	2	SUS 304	
8	HINGE PIN	1	SUS 304	
7	SPLIT PIN	1	SUS 316WS	
6	HEXAGON NUT	1	SUS 304	
5	CONICAL SPRING	1	SUS 316CSP	
4	PLAIN WASHER	1	SUS 316	
3	DISC ARM	1	SCS 13A	
2	DISC	1	SCS 13A	
1	BODY	1	SCS 13A	

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRD 1.5 MPa
PRESS.	MPa	SEAT	ATR 0.6 MPa
TEMP.	℃	ATR	MPa

NAME: JIS 10K WAFER CHECK VALVES
 TYPE: N-258 SIZE: 350 ~ 500 A
 DWG.No. CAWW-0095 ◊ APPROVED BY *Sh. Adachi*
 DATE APR. 17. 2007. CHECKED BY *Sh. Adachi*
 SCALE : DESIGNED BY *R. Matsuki*
 THIRD ANGLE PROJECTION METHOD DRAWN BY *S. Ohya*

△ アイボルト材質変更 H27. 5. 8.

