



| SPEC. | | TEST PRESS. | |
|--------|--------------------------------|-------------|---|
| FLUID | | SHELL | HYDRO 2.1 MPa (21.4kgf/cm ²) |
| PRESS. | MPa (kgf/cm ²) | SEAT | AIR 0.6 MPa (6.1 kgf/cm ²) |
| TEMP. | °C | AIR | MPa (kgf/cm ²) |

END FLANGE: JIS B 2220

| 6 | O RING | 1 | NBR | |
|--------------------------------------|----------------|-------------|-------------------|---------|
| 5 | HEXAGON BOLT | 6 | SUS 304 | |
| 4 | GASKET PACKING | 1 | P.T.F.E | |
| 3 | DISC | 1 | SUS 304 | |
| 2 | STRAINER | 1 | SCS 13A | |
| 1 | BODY | 1 | SCS 13A | |
| No. | NAME OF PARTS | Q.TY | MATERIALS | REMARKS |
| NAME JIS 10K FLANGED END FOOT VALVES | | | | |
| TYPE | N-215 | SIZE | 50A | |
| DWG.No. | FAFS-0157 | APPROVED BY | <i>K. Tanaka</i> | |
| DATE | APR. 12. 2007 | CHECKED BY | <i>G. Asakura</i> | |
| SCALE | : | DESIGNED BY | <i>R. Matsuki</i> | |
| THIRD ANGLE PROJECTION METHOD | | | DRAWN BY | |

O. N. INDUSTRIES LTD.