



SIZE	PIPE THREAD	H	L	S	Q.TY
	d				
2 <sup>1</sup> / <sub>2</sub> B	Rc 2 <sup>1</sup> / <sub>2</sub>	182	180	90	
3B	Rc 3	208	217	105	

SPEC.		TEST PRESS.	
FLUID		SHELL	HYORO 2.1 MPa (21.4kgf/cm <sup>2</sup> )
PRESS.	MPa ( kgf/cm <sup>2</sup> )	SEAT	AIR 0.6 MPa (6.1 kgf/cm <sup>2</sup> )
TEMP.	°C		AIR ( MPa kgf/cm <sup>2</sup> )

PIPE THREADS: JIS B 0203  
No.6 3B Q.TY: 8

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
9	BEARING	2	P. T. F. E	+SUS316
8	GASKET PACKING	1	P. T. F. E	
7	O RING	1	NBR	
6	HEXAGON BOLT	6	SUS 304	
5	PIN	1	SUS 304	
4	DISC	1	SCS 13	
3	SEAT	1	SCS 13	
2	STRAINER	1	SCS 13	
1	BODY	1	SCS 13	

NAME	JIS 10K SCREWED END FOOT VALVES		
TYPE	N-210	SIZE	2 <sup>1</sup> / <sub>2</sub> B, 3B
DNQ.No.	FASS-0041	APPROVED BY	Y.SATO
DATE	JUN. 12, 1993	CHECKED BY	K.TSUNETO
SCALE	:	DESIGNED BY	K.TSUNETO
THIRD ANGLE PROJECTION METHOD	DRAWN BY		

△		
△	SI 单位记变更	'99. 9. 16.
△	BEARING	'94. 4. 18.

**O. N. INDUSTRIES LTD.**