



Q. TY: \_\_\_\_\_

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 2.1 MPa (21.4 kgf/cm <sup>2</sup> )
PRESS.	MPa ( kgf/cm <sup>2</sup> )	SEAT	AIR 0.6 MPa (6.1 kgf/cm <sup>2</sup> )
TEMP.	°C	AIR	MPa ( kgf/cm <sup>2</sup> )

END FLANGED: JIS B 2220

19	GLAND SLEEVE	1	SUS 316	
18	STUD BOLT, NUT	4	SUS 304	
17	GLAND BOLT	2	SUS 304	
16	BODY CAP BOLT	4	SUS 304	
15	HANDLE	1	SCS 13	
14	STOP RING	1	SUS 304	
13	STOPPER	1	SUS 304	
12	STEM BEARING	1	P.T.F.E.	GLASS FILLED
11	GLAND PACKING	1SET	P.T.F.E.	
10	THRUST BEARING	1	P.T.F.E.	GLASS FILLED
9	GASKET PACKING	1	P.T.F.E.	
8	BALL SEAT	2	P.T.F.E.	GLASS FILLED
7	PAD PACKING	1	P.T.F.E.	GLASS FILLED
6	GLAND	1	SCS 13	
5	STEM	1	SUS 316	
4	BALL DISC	1	SCS 14A	
3	TANK PAD	1	SCS 14A	
2	BODY CAP	1	SCS 14A	
1	BODY	1	SCS 14A	

No.	NAME OF PARTS	Q. TY	MATERIALS	REMARKS
NAME JIS 10 K F.F. FLANGED END STRAIGHT WAY TANK BALL VALVE				
TYPE N-765		SIZE 40 A		
DWG. No.	BABS-0277	APPROVED BY	<i>K. Hanita</i>	
DATE	APR. 02. 2007.	CHECKED BY	<i>A. K. K. K.</i>	
SCALE	:	DESIGNED BY	-	
THIRD ANGLE PROJECTION METHOD		DRAWN BY <i>K. K. K. K.</i>		

**O. N. INDUSTRIES LTD.**